

SUMMARY

<u>STATCOM DC-Link Fuzzy Controller for Power Factor Correction -</u> <i>B. Ferdi, C. Benachaiba, B. Berbaoui, R. Dehini</i>	173
<u>Torque Ripple Minimization of 4 Phases 8/6 Switched Reluctance Motor Drive with DTC -</u> <i>P. Srinivas, P.V.N. Prasad</i>	179
<u>A Simulation Study of the Gas Characteristics Effect on Surface Discharges Apparition between Electrode and Dielectric Layer -</u> <i>T. Seghier, Fatima Bouchelgua, B. Zegnini</i>	185
<u>Etude du transfert d'énergie pile à combustible-charge -</u> <i>F.Z. Zerhouni, M. Zegrar, M.T. Benmessaoud, A. Boudghene Stambouli</i>	190
<u>Influence of DC-Link Capacitor Aging on the PWM Converters Operation -</u> <i>R. Marschalko, D. Fodor, P.D. Teodosescu, M. Bojan</i>	197
<u>Electrical Equipment for Indoor Lighting Installations -</u> <i>Adina Filip, V. Maier, S.G. Pavel, D. Pop</i>	203
<u>Asynchronous Motors Behavior under Harmonics -</u> <i>H.G. Beleiu, S.G. Pavel, D. Leşe</i>	209
<u>State of the Art in the Optimal Design of Electromagnetic Devices -</u> <i>R. Cherecheş, V. Ţopa, M. Purcar, Laura Grindei, A. Avram</i>	215
<u>Optimal Design of a Switched Reluctance Motor using the XFEM Method -</u> <i>V. Ţopa, M. Purcar, C. Munteanu, Laura Grindei, A. Avram, R. Cherecheş</i>	222
<u>Synchronous Detection Technique for Multiphase Voltage and Currents System Phasors Alignment Method -</u> <i>G. Todoran, R.A. Munteanu</i>	227

